

Instructions for Packing and Delivery

09/21

In Order to avoid problems on reception of goods and to guarantee faultless operation in our storage facilities, please observe the following instructions:

1. Loading Aid

- The only loading aids permitted are perfect condition EURO-POOL pallets (800x1200 mm UIC Code 435-2) or other separate between both parties agreed loading aids.

2. Arrangement and Security of Pallets Loads

- The load must not exceed the basic dimensions of the pallet 800x1200 mm, neither is it to exceed the loading height of 800 mm.
- A max. load size of 760x1160x760 mm must be observed so as to take into account possible bulging of cardboard boxes.
- A suitable load securing device is required. Aids to secure the load (edge-guards, straps) must not exceed the specified load size.
- It is only allowed to use crystal-clear strink foil and recyclable cardboard boxes.
- Wherever possible, cardboard boxes must be stacked on the pallet in interlocking bond form to improve the stability of the load.
- Cardboardboxes have to be placed at the pallet, that the label is readable from its front face.



3. Identification of Packaging Units

- Each cardboard box must carry on its front face information after conditions (order no., supplier no.) from Engel and it must be clearly readable. Please just use the supplier number, not the supplier name.
- Each pallet must be marked with the contents.

4. Sealing of packaging units

- It is in the responsibility of the supplier to take care that all packing units are completely sealed to avoid that the packing units can open by themselves.

5. Weight per Packaging Unit

- The gross weight of an individual packaging unit must not exceed 15 kg, especially to consider for drawing part, special part...

6. Maximum Weight per Pallet (Loading aids + load)

- The max. weight of 800 kg is not allowed to exceed.



VERBINDUNGSELEMENTE ENGEL GmbH

Weltestraße 2 + 4
88250 Weingarten, Germany

Telefon: +49 751 407-0
Telefax: +49 751 47250

www.schrauben-engel.de
engel@schrauben-engel.de

VERBINDUNGSELEMENTE ENGEL GmbH
Postfach 3054, 88216 Weingarten, Germany

7. Form of Packaging

- Once they have been used and approved, the same packaging must be used to for all future deliveries. Changes are only possible after prior agreement with us.
- We do not accept oil pollute packaging, neither barrels nor boxes.
- We insist on deliveries general in commercial quality packaging. The quality of the packaging must be agreed with the demand of contents.

8. Deliveries by truck

- We cannot unload stacked pallets, we also unload the truck only from the truck rear with the ramp height of 1-1,60 m.
- We do not unload truck in our yard.

9. Pallet pattern

- With more than one product for each pallet, the pallet must be divided into two parts in the lengthwise.
- Different products are separated with a carton.
- Special case for threades rods.

10. Container Loading

- Please use EURO-POOL pallets (800x1200 mm UIC Code 435-2).
- Neutral packaging without any prints on it and labelled also neutral without our company name.

11. Fumigation of wooden pallets

- Verbindungselemente Engel GmbH only accepts heat treated (core temperature 56°C for min. 30 minutes) or pressed wooden pallets. It is strictly forbidden to fumigate the wooden pallets with Methyl Bromide.

12. Prohibition of Dimethylfumarate (DMF)

- According to the EU-Commission decision 2009/251/EC it is strictly forbidden to use products or substances containing DMF (for example contained in SILICA-GEL packet).